



NOMINAL KV	L	R	S1	S2	S3	T1	T2	T3	BIL Ø TO Ø & Ø TO GRD	BIL RATING OF CONTACT
15									95	95
APPROX. WT.-LBS.	CAT.# 4800_9M1WY									3165

NOTES:

1- THE TRAYER CAT.# 901A LIQUID LEVEL GAUGE IS A COMPLETELY STATIC DEVICE THAT ACTUALLY READS "LOW OIL" IF THE OIL DROPS BELOW PROPER LEVEL IT IS AVAILABLE TO ALL SWITCH AND TRANSFORMER MANUFACTURERS IN ORDER TO PROMOTE INDUSTRY STANDARDIZATION.

2- DECAL READS:
"BREAKER TRIPPED WHEN YELLOW INDICATOR PROJECTS IN TO THE SIGHT GLASS. TO RESET BREAKER, OPEN AND CLOSE OPERATING HANDLE"

3- DECAL READS:
LIQUID LEVEL INDICATOR READS "LOW OIL" WHEN OIL IS LOW.

4- DECAL READS:
FILLED WITH NON PCB MINERAL OIL [LESS THAN 1 PPM] AT TIME OF MANUFACTURE

5- MATERIAL:
OIL TANK : 7 GA. STAINLESS STEEL
CABINET & BASE : 11 GA. STAINLESS STEEL

TRAYER S.O.

CATALOG LETTER INSERT	BUSHING AMPERE				FINISH DARK GREEN ENAMEL	TRAYER ENGINEERING CORPORATION 898 PENNSYLVANIA AVENUE SAN FRANCISCO, CALIFORNIA 94107 (415) 285-7770	
	L	R	S	T	MATL. SEE NOTE# 5		
	A	200	200	200	200		SCALE 1/8" = 1"
	B	600	600	200	200		DR. BY F. LESPADE
	C	600	600	600	600		CK. BY BJB
D	600	200	200	200	APPVD. BJB	15 KV TRAYER CAT.#4800_9M1WY 4 WAY SUBMERSIBLE VACUUM FAULT INTERRUPTER AND VACUUM SWITCH WITH 6-1Ø VACUUM FAULT INTERRUPTERS	
E	600	600	600	200	DATE 08-28-08		
TOLERANCES ± 1/8"					UNIT TYPE PADMOUNT	DRAWING NUMBER 080807	
						REVISION B 10-17-08	