



**NOTES:**

1- THE TRAYER CAT.# 901C LIQUID LEVEL GAUGE IS A COMPLETELY STATIC DEVICE THAT ACTUALLY READS "LOW OIL" IF THE OIL DROPS BELOW PROPER LEVEL IT IS AVAILABLE TO ALL SWITCH AND TRANSFORMER MANUFACTURERS IN ORDER TO PROMOTE INDUSTRY STANDARDIZATION.

2- NAMEPLATE READS:  
"BREAKER TRIPPED WHEN YELLOW INDICATOR PROJECTS IN TO THE SIGHT GLASS. TO RESET BREAKER, OPEN AND CLOSE OPERATING HANDLE"

3- DECAL READS:  
FILLED WITH NON PCB MINERAL OIL [LESS THAN 1 PPM] AT TIME OF MANUFACTURE

4- MATERIAL:  
OIL TANK : 7 GA. STAINLESS STEEL

CATALOG NO.	NOMINAL KV	BIL Ø TO Ø & Ø TO GRD	BIL ACROSS OPEN CONTACT	APPROX. GROSS WEIGHT - LBS.
CAT.# 4102-2_M2	15	95	95	2530

CATALOG LETTER INSERT	BUSHING AMPERE			
	L	R	T	S
A	200	200	200	200
B	200	200	600	600
C	600	600	600	600
D	200	200	200	600

TOLERANCES ± 1/8"

TRAYER S.O.

FINISH: NATURAL	TRAYER ENGINEERING CORPORATION 898 PENNSYLVANIA AVENUE SAN FRANCISCO, CALIFORNIA 94107 (415) 285-7770
MATL: SEE NOTE # 4	
SCALE: 1/4" = 1"	
DR. BY: R.KOWDLEY	
CK. BY: BQB	15 KV TRAYER CAT.#4102-2_M2
APPVD: BQB	4 WAY SUBMERSIBLE VACUUM FAULT INTERRUPTER AND VACUUM SWITCH WITH 6-1Ø VACUUM FAULT INTERRUPTERS
DATE: 03-07-08	DRAWING NUMBER: 070230
UNIT TYPE: SUBMERSIBLE	REVISION: C
	10-08-08