



- NOTES:
- 0 TO 15 PSIG PRESSURE GAUGE. SEE CHART FOR TEMPERATURE CORRECTION.
 - MATERIAL:
TANK : 7 GA. STAINLESS STEEL
 - THIS PORT CONTAINS A DILO VALVE WHEN UNIT IS SF6 INSULATED.
 - NAMEPLATE READS:
"BREAKER TRIPPED WHEN YELLOW INDICATOR PROJECTS IN TO THE SIGHT GLASS. TO RESET BREAKER, OPEN AND CLOSE OPERATING HANDLE"
 - NAMEPLATE READS:
"POTENTIAL TRANSFORMER DISCONNECT SWITCH MUST BE IN OPEN POSITION WHEN DOING HIGH POTENTIAL TESTING."
 - WEIGHT OF UNIT : 1490 LBS.

				TRAYER S.O.		TRAYER ENGINEERING CORPORATION 898 PENNSYLVANIA AVENUE SAN FRANCISCO, CALIFORNIA 94107 (415) 285-7770	
CATALOG LETTER INSERT	BUSHING AMPERE				FINISH NATURAL		TRAYER 15 KV SUBMERSIBLE SELF-CONTAINED SF6 INSULATED VACUUM SWITCHGEAR ASSEMBLY CAT.#G3102-2BVDG4M1
	WAY 1	WAY 2	WAY 3	WAY 4	MATL. SEE NOTE# 2 SCALE 1/8" = 1"		
A	200	200	200	200	DR. BY F. LESPADE		DRAWING NUMBER 080924
B	600	600	200	200	CK. BY <i>BAB</i>		
C	600	600	600	600	APPVD. <i>BAB</i>		
D	600	200	200	200	DATE 09-26-08		
E	600	600	200	600	UNIT TYPE SUBMERSIBLE		REVISION A

TOLERANCES ± 1/8"